

## **KENNELS / CATTERIES / HANDLING CAGES**

---

To completely remove the odour, NokOut must come into direct contact with the problem

**IMPORTANT:** Always do a patch test to check for colour fastness. OdorTECH cannot be responsible for any issues of discolouration, fading, etc. May cause fading if exposed to direct sunlight before fully dry.

### **SHAKE BOTTLE WELL BEFORE USING:**

**KENNELS:** Add 175 – 250 ml of **NokOut** to 4 litres of water and mop or wipe down the kennel area. You can also spray or fog a fine mist over the entire area and let dry – **NokOut** will provide up to 24 hours of residual odour control. When spraying, ensure that all areas are covered including fencing, ceilings, and walls. For air borne odours, dilute 250 ml of **NokOut** into 4 litres of water and put in a cold vaporizer, allowing it to run for a maximum of 4 hours; shut off and let **NokOut** work. For floor drains, pour 30 – 60 ml of **NokOut** directly into the drain.

**NokOut** can also be used to wash toys, and food and water bowls.

**CATTERIES:** For the first application, spray the entire area liberally with **NokOut** at full strength, ideally using a fog or misting machine. Floors may be mopped with a solution of 250 ml of **NokOut** to 4 litres of water.

**HANDLING CAGES:** Wipe down with a 50/50 **NokOut** and water solution.

**LITTER BOXES:** Spray the bottom of an empty, clean litter box liberally with **NokOut**. Allow the product to dry and repeat until there is no odour in the plastic itself. Fill the box with litter and lightly spray the top of the litter with **NokOut**. Once or twice a day, clean the litter and do a light spray of **NokOut** onto the litter. **NokOut** has a residual effect – it continues to fight odours long after it has dried. **NokOut** will extend the life of your cat litter because the litter box will remain cleaner for longer than if you didn't use **NokOut**, and no odours will disturb your cat.

**VEHICLE TREATMENT:** Spray into the air intakes for the heater and air conditioning system. This should be done with the windows rolled up, engine running and the heat or air conditioning fan turned on high. Atomize **NokOut** into the cabin area, spray the interior starting with the headliner and let the vehicle run for 3-5 minutes. Once done, roll down the windows or open the door and let the vehicle air out for a few minutes.

**SKUNK TREATMENT:** Refer to the “**HOW TO DE-SKUNK AN ANIMAL**” instruction sheet.

**NokOut works as it dries so let it dry thoroughly!**